



Aircol 2294

Synthetic refrigeration compressor lubricant

Description

Castrol Aircol™ 2294 is a synthetic refrigeration oil formulated from selected polyalphaolefin base fluids.

Application

Aircol 2294 is specifically designed for refrigeration systems using screw type compressors in conjunction with very low evaporation temperatures. Aircol 2294 may also be specified for certain systems using reciprocating compressors with high compression ratios and high discharge temperatures.

The very low pour point enables Aircol 2294 to be used in systems where evaporator temperatures are extremely low. However because of low miscibility with R22, Aircol 2294 is not suitable for use in refrigeration systems using flooded evaporators, unless efficient oil separators or some other method of oil recovery is provided.

Conditions of Use

- Low miscibility and solubility with R22 - gives significant advantages in screw type compressors where refrigerant absorption can reduce lubricant viscosity to unacceptably low levels.
- Very low Pour Point - allows the use in refrigeration systems with extremely low evaporator temperatures.

Typical Characteristics

Name	Method	Units	Aircol 2294
Appearance	Visual	-	Clear liquid
Density @ 20°C / 68°F	ISO 12185 / ASTM D4052	kg/m ³	835
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	68
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	10.7
Viscosity Index	ISO 2909 / ASTM D2270	-	147
Pour Point	ISO 3016 / ASTM D97	°C/°F	-50/-68
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	235/455

Subject to usual manufacturing tolerances.

Aircol 2294

06 Feb 2025

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine