



Product Data

CASTROL AIRCOL SW RANGE

Synthetic refrigeration compressor lubricant

Description

The Castrol Aircol SW range of synthetic refrigeration lubricants are formulated from polyolester base stocks.

Application

They are specifically designed for use with refrigeration systems using environmentally friendly HFC refrigerants, in particular R134a.

Features / Benefits

The synthetic base stocks used in the Aircol SW range are fully miscible with HFCs, in particular R134a, even at temperatures well below the minimum likely to be encountered in service.

The Aircol SW grades have been formulated to enhance hydrolytic stability, load carrying and inhibition against copper plating. They are wax free and hence have very low pour points. This ensures the evaporator remains clean (consequent efficient heat transfer) and reduces the risk of pipe blockages.

Technical Data

Name	Method	Units	Aircol SW 32	Aircol SW 46	Aircol SW 68	Aircol SW 100	Aircol SW 170	Aircol SW 220
Density at 20°C	ASTM D1298	g/ml	0.977	0.98	0.98	0.969	0.968	0.975
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	32	46	68	100	170	220
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	5.4	6.9	8.5	11.4	17	19
Pour Point	ASTM D97	°C	-46	- 42	-39	- 30	- 27	- 27
Closed Flash Point	ASTM D93	°C	233	235	245	235	235	250

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CASTROL AIRCOL SW RANGE

01 Jun 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine