



Product Data

Cyltech 70

Crosshead engine cylinder oil

Description

Castrol Cyltech 70 is a marine diesel engine cylinder lubricant developed to provide good performance at the higher temperatures and pressures found in modern engines.

Application

Cyltech 70 is suitable for the cylinder lubrication of low speed crosshead engines burning residual fuels. Cyltech 70 can be used with a wide range of fuels with sulphur content typically between 0.1% and 3.5% when feed rates are adjusted appropriately. Please consult the engine makers for specific advice.

Castrol Cyltech ACT should be used with fuels having a sulphur content below 0.1%.

Advantages

- Excellent performance, even at optimised lubricant feed rates.
- Excellent control of piston ring and cylinder liner wear.
- High level of piston, piston ring and cylinder liner cleanliness.
- Good thermal and oxidative stability.

Product Performance Claims

Cyltech 70 has 'No Objection' status with the principal manufacturers of crosshead engines for use under conditions as specified in their current oil recommendation lists.

Typical Characteristics

Name	Method	Units	Cyltech 70
Density @ 15°C, Relative	ASTM D1298	g/ml	0.934
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	19.5
Base Number, BN	ASTM D2896	mg KOH/g	70
Flash Point, PMCC	ASTM D93	°C	>190
Pour Point	ASTM D97	°C	-9
SAE Grade			50

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Cyltech 70
07 Nov 2017
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine